



## 2010 PRIMAL SPEC SHEET

by NEG as of 12/01/09

**A/A:** 32-1/8" +/- 3/16"

**String:** 56"

**B.H.:** 7" +/- 1/8"

**Cable:** 36-11/16"

MODS <sup>1</sup> :	DRAW LENGTH <sup>2</sup> :	IBO RATING <sup>3</sup> :
SYNC-#1	30"	330-325
SYNC-#2	29.5"	325-320
SYNC-#3	29"	320-315
SYNC-#4	28.5"	315-310
SYNC-#5	28"	310-305
SYNC-#6	27.5"	305-300
SYNC-#7	27"	300-295
SYNC-#8	26.5"	295-290

Limb Deflections:	Limb Weights:	Limb Lengths:
70-74	50-53	13"-Solid Pinned
86-90	60-63	13"-Solid Pinned
98-102	70-73	13"-Solid Pinned

**Cam System:** SYNC Cam System  
**Let-Off:** 80%  
**Speed Studs:** 30gr. @ 2" from tip of each cam.  
**Spacers:** .045" on cable side  
**I-Glide Rod:** 7.125"(4 grooves)  
**Suppressor Rod:** 6.9"(4 groove) set @ 1/16" from string  
**Bearings:** Flanged - P/N:12216  
**Pivots:** 0.162"(Blue)

Notes:

- 1.) Cam designation "A" goes on top of R.H. model, where "B" goes on top for L.H. model.
- 2.) Minus nothing, plus 1/4"
- 3.) Measured with 350-grain arrow @ 70#.