



2011 REV SPEC SHEET

by NEG as of 4/18/11

A/A: 32-1/8" +/- 3/16"

String: 56"

B.H.: 7-5/8" +/- 1/8"

Cable: 36-11/16"

MODS¹:	DRAW LENGTH²:	IBO RATING³:
SYNC-#1	30.5"	325-320
SYNC-#2	30"	320-315
SYNC-#3	29.5"	315-310
SYNC-#4	29"	310-305
SYNC-#5	28.5"	305-300
SYNC-#6	28"	300-295
SYNC-#7	27.5"	295-290
SYNC-#8	27"	290-285

Limb Deflections:	Limb Weights:	Limb Lengths:
75-79	50-53	13.5"-Solid Pinned
93-98	60-63	13.5"-Solid Pinned
112-118	70-73	13.5"-Solid Pinned

Cam System: SYNC Cam System
Let-Off: 80%
Speed Studs: 30gr. @ 2" from tip of each cam.
Spacers: .045" on cable side
Cable Guard: 8.5" carbon rod w/ black Alpine slide
Suppressor Rod: 6.9"(4 groove) set @ 1/16" from string
Bearings: Flanged - P/N:12216
Pivots: 0.162"(Blue)

Notes:

- 1.) Cam designation "A" goes on top of R.H. model, where "B" goes on top for L.H. model.
- 2.) Minus nothing, plus 1/4"
- 3.) Measured with 350-grain arrow @ 70#.