



## **2013 DRIVE SPEC SHEET**

by SP as of 7/16/13

**A/A:** 33 1/4" +/- 3/16"

**String:** 60 3/4"

**B.H.:** 7 1/8" +/- 1/8"

**Cable:** 40 1/8"

<b>MODS<sup>1</sup>:</b>	<b>DRAW LENGTH<sup>2</sup>:</b>	<b>IBO RATING<sup>3</sup>:</b>
FLUX #1	30"-31"	330-325
FLUX #2	29"-29.5"	320-315
FLUX #3	28"-28.5"	310-305
FLUX #4	27"-27.5"	300-295
FLUX #5	26"-26.5"	290-285

<b>Limb Deflections:</b>	<b>Limb Weights:</b>	<b>Limb Lengths:</b>
103-107	50-53	13.5" Solid Pinned
125-129	60-63	13.5" Solid Pinned
158-162	70-73	13.5" Solid Pinned

**Cam System:** FLUX Cam System  
**Let-Off:** 70%  
**Speed Studs:** 12 gr. @ 2" from tip of each cam.  
**Spacers:** .100" on cable side -Black  
**Cable Guard:** Carbon Steel Flex- P/N: W-000146  
**Suppressor Rod:** 5/16" Carbon Rod w/ Bumper  
**Bearings:** Flanged - P/N:12216  
**Pivots:** 0.162"(Blue)

Notes:

- 1.) Cam designation "A" goes on top of R.H. model, where "B" goes on top for L.H. model.
- 2.) Minus nothing, plus 1/4"
- 3.) Measured with 350-grain arrow @ 70#.